

RB800

PROGRAMMABLE, LOW COST GSM/GPRS/UMTS TERMINALS

The RB800 terminal series is the complete modem solution for wireless m2m applications. Based on the high quality module, it is available as DUAL or QUAD band versions and offers high level GSM/GPRS/UMTS features in a compact aluminum housing with all the standardized interfaces and optionally GPIO, SD memory card, backup battery or dual SIM option. Together with its small size and wide supply voltage range, it makes it easy to integrate into all kinds of machines.

TELEORIGIN
UNIQUE TECHNOLOGY FOR TELEMETRY



THE RB800 MODEM SERIES

The RB800 modem series enabling voice, eCall, data, SMS and fax communication is a universal solution for all low-volume M2M and mobile data applications including metering, traffic systems, transportation and logistics, security, vending machines, and facility management.



The device can be controlled by standard AT commands or by customer's application inside (embedded Python Script Interpreter), thus making it the smallest, complete SMT platform for M2M solutions.

KEY BENEFITS

authorized partner:
ELTRONIKA sp. z o.o | www.eltronika.com
info@eltronika.com | post@eltronika.cz
tel. +48 227519744 | +420 228880487

FAST TIME TO-MARKET

BEST PRICING
LEVEL

EXTENDED POWER
SUPPLY RANGE

EASY WIRELESS
APPLICATION

LOW POWER
CONSUMPTION

FEATURES

RS232 & USB interfaces
Audio support
SMA antenna
Dual SIM, GPIO, SD card, Battery
Telit AT command set
Python Script Interpreter
m2mLOCATE, m2mAIR, m2mCLOUD

SPECIFICATION:

- Ideal for connecting devices with RS232 or RS485:
 - Vending Automation - Industrial control
 - Sensors - Alarms
 - Telemetry - Remote control
- Serial UART or USB interface
- SMA antennas connector

- Power supply from 5 to 30V DC
- Extremely compact (only 83 x 53.3 x 26 mm)
- Quad Band = can be used worldwide
- Perfect with customer APN and m2mAIR SIM cards
- Embedded TCP/IP and UDP stacks
- Control via AT commands or Python application

OPTIONAL ACCESSORIES:

- External antenna
- Power supply and customized connection cable
- Optional internal backup battery
- DIN mounting
- Wall mounting

Network	Model	Speed	Interface			GPIO		Dual SIM	SD card	Function			Python	Audio	Battery
			RS232	RS485	USB	In / Out	Analog in			SMS	Email	CSD			
2G	RB800	85.6 kBit/s	•	○	-	-	-	○	-	•	•	•	•	•	-
	RB800-IO	85.6 kBit/s	•	○	-	7	○5	○	-	•	•	•	•	•	-
	RB800-M	85.6 kBit/s	•	○	-	-	-	○	•	•	•	•	•	•	-
	RB800-IO-M	85.6 kBit/s	•	○	-	7	○5	-	•	•	•	•	•	•	○
	RB800WR	85.6 kBit/s	•	○	-	-	-	○	-	•	•	•	•	•	-
3G	RB800U	7.2 Mbit/s	•	○	•	-	-	○	-	•	•	-	•	-	-
	RB800U-M	7.2 Mbit/s	•	○	•	-	-	○	•	•	•	-	•	-	-
	RB800U-IO	7.2 Mbit/s	•	-	•	7	○5	-	-	•	•	-	•	-	○

• support ○ option - not support